

SHWG02I304072A

WOLF GRAPHICS I3200 2PH 4C – 72"



High-Performance Large Format Printing System: Advanced eco-solvent printing technology designed for large-format production, delivering consistent color output, high efficiency, and reliable performance for demanding printing environments.

Dual-Printhead Industrial Configuration: Equipped with 2 high-precision Epson I3200 printheads, ensuring sharp detail, smooth gradients, and stable performance across continuous production workflows.

Professional CMYK Color System: 4-color CMYK eco-solvent ink configuration optimized for strong color consistency, high durability, and vibrant output across a wide range of advertising materials.

High-Speed Production Workflow: Optimized printing modes designed to balance speed and quality, enabling efficient production for banners, vinyl, signage, and large-format graphics.

Advanced Ink Management System: Integrated ink supply system designed to maintain stable ink flow, reduce maintenance issues, and ensure reliable long-term operation.

Professional RIP Software Included : Advanced color management, ICC profile optimization, and workflow automation for precise, efficient, and scalable production control.

Printing System

Technology: Eco-solvent inkjet printing
Printhead Configuration: 2 printheads
Ink Type: CMYK – QUALITINK Eco-solvent
Maximum Print Width: Up to 180 cm (70.8")

Printing Speed

Draft Mode: Up to 30 m/h ($\approx 45 \text{ m}^2/\text{h}$)
Production Mode: Up to 26 m/h ($\approx 39 \text{ m}^2/\text{h}$)
Quality Mode: Up to 16 m/h ($\approx 24 \text{ m}^2/\text{h}$)

Speeds may vary depending on media type, ink coverage, and operation conditions.

Format & Materials

Compatible Materials:
Vinyl
Banner
Photo paper
Backlit film
Panaflex
Perforated vinyl
Synthetic leather
Blackout banner

Ideal for large-format signage and advertising applications

Power & Electrical

Voltage: 220 V + UPS (required)
Frequency: 50 – 60 Hz
Total Power Consumption: 3.2 kW
Drying System Power: 3.2 Kw

Drying System

Integrated heating and drying system
Ensures fast ink curing and stable production output

Software & Workflow

Professional RIP software included
Optimized for:
Color consistency
Efficient job processing
Large-format workflow control

Working Environment

(No especificado en el PDF, se mantiene estándar técnico recomendado)

Recommended Temperature: 18°C – 25°C
Recommended Humidity: 40% – 70%

Warranty

Not specified

Applications

Large-format advertising
Signage and banners
Indoor & outdoor graphics
Retail displays
Backlit signage

Fume Extraction System

Not specified

Not specified

Power Consumption

Not specified