Shurez®
Print Sure, Print Shurez

SPEC SHEET
UV DTF

SHRU03I306024A

RACCOON UV DTF TEXTILE

UV DTF PRINTING TECHNOLOGY



23.6 in Print width	3–4 Printheads
29 ft²/h Max. speed	CMYK + W + V Inks + neon

TECHNICAL OVERVIEW

The RACCOON UV DTF TEXTILE 23.6 in is a professional 23.6 in digital printing system designed for DTF production with high precision and continuous output. It integrates i3200U1 printheads and a CMYK + White + Varnish ink setup.

PRINT MODES · UP TO* CMYK + W + V

	6 PASSES		8 PASSES	
MODE	linear ft/h	Area	linear ft/h	Area
Draft	4.5	**29 ft²**	3	**19 ft²**
Production	3	**19 ft²**	2	**13 ft²**
Quality	2	**13 ft²**	1	**6.5 ft²**

PRINT MODES · UP TO* CMYK + 2W + V

	6 PASSES		8 PASSES	
MODE	linear ft/h	Area	linear ft/h	Area
Draft	7	**46 ft²**	5.5	**32 ft²**
Production	5	**32 ft²**	3.5	**22 ft²**
Quality	2.5	**16 ft²**	2	**13 ft²**

* Speeds may vary depending on the print type and the number of white and varnish layers. These speeds are for 4 layers of white.

APPROX. DIMENSIONS

↔	⤢	↕	
78.7 in Width	32.3 in Depth	62.2 in Height	441–529 lb Weight

TECHNICAL SPECIFICATIONS

Printhead	3 printheads (CMYK + White + Varnish) 4 printheads (CMYK + White + Varnish + Neon) 4 printheads (CMYK + 2 Whites + Varnish) 4 printheads (CMYK + White + 2 Varnish)
Inks	CMYK + White + Varnish + Magenta Neon + Yellow Neon
Print width	Up to 24 in
Print media	TPU, vinyl, etc.
Laminating material	Transfer film
Interface	Gigabit network port transmission
Electrical requirements	1 × 220 VAC connection
RIP software	Professional RIP software - included
Compatible files	PDF, JPG, TIFF, etc.