Shurez®
Print Sure, Print Shurez

SPEC SHEET
DTF PRINTING

SHRD03I305024A

ROOSTER DTF 2403NEON

DTF PRINTING SYSTEMS



23.6 in Print width	3 × I3200 Printheads
97 ft²/h Max. speed	CMYK + W + N Inks + neon

TECHNICAL OVERVIEW

The SHUREZ ROOSTER DTF I3200 Series A is a professional 24" DTF printer designed to deliver speed, precision and quality in textile production. Its system streamlines fashion, advertising, footwear and customization work.

PRINT MODES · UP TO*

	6 PASSES		8 PASSES	
MODE	linear ft/h	Area	linear ft/h	Area
Draft	15	**97 ft²**	11	**71 ft²**
Production	12	**78 ft²**	8	**52 ft²**
Quality	8	**52 ft²**	5	**32 ft²**

FILTERS · EXTERNAL EXTRACTOR



Cotton filter
Every 7 to 15 days



Foam filter
Monthly



HEPA filter
Every 3 months



Main carbon filter
Every 6 months

FILTERS · SMART OVEN



Air filter
Smart oven
Monthly



Carbon filter
Smart oven
Every 3 months

APPROX. DIMENSIONS

↔ 78.7 in Width	⤢ 70.9 in Depth	↕ 57.1 in Height	551–661 lb Weight	Oven Automatic
↔ 78.7 in Width	⤢ 104 in Depth	↕ 57.1 in Height	772–882 lb Weight	Oven Smart

TECHNICAL SPECIFICATIONS

Printhead	3 printheads - I3200
Inks	CMYK + White + Neon
Print width	Up to 24 in
Print media	PET film / DTF paper
Fume extractor	Included - external (automatic oven) Included - internal (smart oven)
Applications	Fashion, apparel, advertising and footwear.
Oven	Automatic Smart At customer's choice
Machine power	4 kW - automatic oven (total consumption) 6.5 kW - smart oven (total consumption)
Operating environment REQUIRED	Temperature: 73–84 °F Humidity: 35-65%
RIP software	Professional RIP software - included
Sensors (ink level)	Included
Heat platen	Plotter: Included Oven: Included
Electrical requirements REQUIRED · STABLE	1 × 220 VAC connection (plotter) 1 × 220 VAC connection (oven) 1 × 220 VAC connection (extractor) (automatic oven).