Shurez®
Print Sure, Print Shurez

SPEC SHEET
UV HYBRID

SHKU03I306024NA

SHARK UV HYBRID60x90

UV PRINTING · RIGID & FLEXIBLE



23.6 × 35.4 in Print area	3 × I3200U1 Printheads
90 ft²/h Max. speed	CMYK + W + V Inks

TECHNICAL OVERVIEW

A versatile printer designed to create custom pieces with high-quality finishes on many types of materials. Ideal for expanding your production capabilities and creating products with strong visual impact.

PRINT MODES · UP TO*

	6 PASSES		8 PASSES	
MODE	linear ft/h	Area	linear ft/h	Area
Draft	14	**90 ft²**	10	**65 ft²**
Production	10	**65 ft²**	7	**45 ft²**
Quality	5	**32 ft²**	4	**26 ft²**

* Speeds may vary depending on the print type and the number of white and varnish layers.
* These speeds are for a single color layer.

APPROX. DIMENSIONS

↔	⤢	↕	
57.1 in Width	70.9 in Length	51.2 in Height	441–551 lb Weight

TECHNICAL SPECIFICATIONS

Equipment	Hybrid printer 60 × 90. UV printing on rigid and flexible media.
Technology	High-resolution UV. Instant-curing UV inks.
Printhead	I3200U1
Number of printheads	3 printheads
Inks	CMYK + White + Varnish
Print width / area	Up to 23.6 × 35.4 in
Allowed thickness	0–7.1 in Height adjustment for rigid materials.
Frequency	50/60 Hz
Printer power	Up to 2.1 kW
Operating environment REQUIRED	Temperature: 73–84 °F Humidity: 35-65%
RIP software	PRT - PRN
Electrical requirement	1 × 220 VAC connection (plotter) 1 × 220 VAC connection (chiller)
Precision	7.5% (1.5% + 1.5% ×4)
Positioning system * At customer's choice	Automatic with recognition scanner Manual by coordinates / templates
Flatbed	Automatic
Rigid materials	Acrylic, MDF
Flexible materials	Vinyl, banner, TPU, leather.
Compatible software	Illustrator, CorelDRAW and AutoCAD
Optional accessories	Lamination Rotary