Shurez®
Print Sure, Print Shurez

SPEC SHEET
SUBLIMATION

SHSS02I304072A

SNAKE II

TEXTILE SUBLIMATION PRINTER



71.7 in Print width	2 × I3200 Printheads
861 ft²/h Max. speed	CMYK Inks

TECHNICAL OVERVIEW

This industrial printer is designed for wide-format textile sublimation and high-volume production, delivering speed, stability and continuity in demanding workflows. Its wide format handles large pieces and high-capacity rolls, reducing interruptions and supporting long production shifts. Its configuration lets you adjust print speed and quality to each project while keeping results consistent across production levels. It is an ideal solution for fashion, sportswear, home textiles and custom production, providing productivity, versatility and efficiency in industrial environments.

PRINT MODES · UP TO*

MODE	Speed	Area
Draft	164 linear ft/h	861 ft²
Production	115 linear ft/h	603 ft²
Quality	82 linear ft/h	431 ft²

* Speeds may vary depending on design saturation, fabric type and machine operation.

APPROX. DIMENSIONS

↔	⤢	↕	
109 in Width	39.4 in Depth	59.8 in Height	397–507 lb Weight

TECHNICAL SPECIFICATIONS

Printhead	2 printheads - I3200
Inks	CMYK
Print width	Up to 72 in
Print media	Qualitexpaper sublimation paper, rolls up to 656 ft, minimum 60 g/m².
Printer consumption	1 kW
Heater consumption	1.5 kW
Operating environment REQUIRED	Temperature: 73–84 °F Humidity: 35-65%
Frequency	50 - 60 Hz
Sensors (ink level)	Included
RIP software	Professional RIP software
Electrical requirements	1 × 220 VAC connection (plotter) 1 × 220 VAC connection (heaters)
Print formats	PRT - PRN
Tension system	Mechanical