Shurez®
Print Sure, Print Shurez

SPEC SHEET
ECO-SOLVENT

SHWG02I304063A

WOLF GRAPHICS II

GRAPHIC PRINTING



63 in Print width	2 × I3200 Printheads
517 ft²/h Max. speed	CMYK Eco-solvent inks

TECHNICAL OVERVIEW

The SHUREZ WOLF II-63" is a wide-format eco-solvent printer equipped with 2 I3200 printheads and a print width of up to 63 in. It works with Qualitink CMYK eco-solvent inks and supports media such as vinyl, banner, photo paper, perforated vinyl, synthetic leather and other graphic communication substrates. Its system includes a dual heater, adjustable suction and mechanical tension for stable printing. With 3- and 4-pass production modes, it balances speed and quality for each application, making it a versatile solution for advertising, signage and wide-format graphic production.

PRINT MODES · UP TO*

	3 PASSES		4 PASSES	
MODE	linear ft/h	Area	linear ft/h	Area
Draft	30	**517 ft²**	23	**388 ft²**
Production	24	**409 ft²**	18	**301 ft²**
Quality	20	**344 ft²**	15	**258 ft²**

APPROX. DIMENSIONS

↔	⤢	↕	
106 in Width	39.4 in Depth	59.8 in Height	397–507 lb Weight

TECHNICAL SPECIFICATIONS

Printhead	2 printheads - I3200
Inks	CMYK - QUALITINK - Eco-solvent
Print width	Up to 63 in
Print media	Vinyl, banner, photo paper, inkjet backlit film, panaflex, perforated window vinyl, synthetic leather, faux leather and blockout banner.
RIP software	Professional RIP software
Frequency	50 - 60 Hz
Electrical requirement	1 × 220 VAC connection (plotter) 1 × 220 VAC connection (heaters).
Printer consumption	1 kW
Heater consumption	1.5 kW
Print formats	PRT - PRN - PLT
Operating environment REQUIRED	Temperature: 73–84 °F Humidity: 35-65%
Tension system	Mechanical
Sensors (ink level)	Included
Suction system	Adjustable
Heating system	Dual heater